

Technical Data Sheet

CODE 15083

TORRETTA TRT 100 ED 4P

Centrifugal roof fans with horizontal discharge for hot fumes extraction




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed power 1st speed (W)	1400	Weight (Kg)	81,5
Frequency (Hz)	50	Delivery 1st speed (l/s)	2306
Insulation Class	1°	Delivery 1st speed (m³/h)	8300
Max ambient temperature for continuous operation (°C)	50	Max delivery at max speed (l/s)	2528
Max. absorbed Current at max. speed (A)	4,90	Max delivery at max speed (m³/h)	9100
Max. absorbed Current at min. speed (A)	2,30	Pressure - 1st speed (mmH2O)	72
Max. absorbed power at max speed (W)	1950	Pressure - 1st speed (Pa)	706
Motor IP protection	55	Pressure max - max speed (mmH2O)	84
Nominal Diameter (mm)	400	Pressure max - max speed (Pa)	824
Number of Phases (Ph)	3	RPM max	1400
Number of Poles	4	RPM min	1200
Voltage (V)	380-415	Sound Pressure level Lp [dB (A)] 3m	84

DIMENSIONS



Size A (mm)	1015
Size B (mm)	830
Size C (mm)	750
Size D (mm)	449
Size E (mm)	283
Size F (mm)	38
Size G (mm)	40
Size H (mm)	770
Size L (mm)	365
Size M (mm)	375
Size N (mm)	562

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premando 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 15083

TORRETTA TRT 100 ED 4P


Centrifugal roof fans with horizontal discharge for hot fumes extraction



DESCRIPTION

- Centrifugal roof fan suitable for extracting hot fumes at up to 400 °C for 120 minutes.
- Base manufactured from phosphated pressed steel, epoxy powder coated with hammered effect finish, guaranteeing long-term resistance to atmospheric agents.
- Aerodynamically contoured inlet port for optimum performance, fashioned as a single unit with the base and gauged to optimize air flow.
- Motor mounting plate made of steel with galvanization surface treatment.
- Pressed steel motor cover: pickled and phosphated surface, polyester powder coated and oven baked finish, colour grey, with hammered texture.
- Accident prevention and anti-bird grilles (to UNI ISO 13857 standard), consisting of electrically welded steel rings with epoxy powder coated finish, colour black.
- Centrifugal impeller with self-cleaning backward curved blades, dynamically balanced (UNI ISO 1940, Point 1 – Class 6.3), made of electrolytically galvanized pressed steel.
- Dahlander 2 speed three-phase AC motor with shaft turning in ball bearings, size to UNEL MEC standard, flange B5, self-ventilating. Motor insulation class H, with metal cooling fan and cable gland.
- Minimum air flow 8300 m³/h
Maximum air flow: 9100 m³/h.
- Equipped with a motor start capacitor that must be installed remotely from the fan so that it cannot be damaged through direct exposure to heat.
- Galvanized steel eye lugs for transport and lifting/handling operations.
- Cable guaranteeing continuity of earth connection.
- Steel safety wire for anchoring the appliance once installed.


CURVES




ACCESSORIES



IRT 40
Code 12927



TR-G 70/100
(GRIGLIA DI PROTEZIONE)
Code 22506



TR-CU 70/100
(CONTROTELAIO DI BASE U)
Code 22539



TR-CVT
(COMMUTATORE VELOCITA' TRIF.)
Code 22910

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)
Pre & Post Vendita: fax +39 02 90699302
Email prevendita: prevendita@vortice-italy.com