

Cookies help us to provide our services. By using these services, you accept our use of cookies. [Info](#)

[←](#) BACK

CODE 15176

TORRETTA TRT 150 ED-V 6P

Centrifugal roof fans with vertical discharge for hot fumes extraction

- [Description](#)
- [Certifications](#)
- [Technical Data Sheet](#)
- [Accessories](#)

DOCUMENTATION

α






[PRODUCTS](#) > [INDUSTRIAL VENTILATION](#) > [ROOF FANS](#) > [ROOF](#)

Description

- Centrifugal roof fan suitable for extracting hot fumes at up to 400 °C for 120 minutes.
- Base manufactured from phosphated pressed steel, epoxy powder coated with hammered effect finish, guaranteeing long-term resistance to atmospheric agents.
- Aerodynamically contoured inlet port for optimum performance, fashioned as a single unit with the base and gauged to optimize air flow.
- Motor mounting plate made of steel with galvanization surface treatment.
- Protective cap carried by top plate made of steel with galvanization surface treatment.

[Read full description](#)

Certifications

| | | |
|---------------------------------------------------------------------------------------|--------|-------------------|
|  | CE | α |
|  | APPLUS | |
|  | EAC | |

Technical Data Sheet

Technical and performance data

Dimensions

Curves

| | | | |
|-------------------------------------------------------|------|-----------------------------------------------|-------|
| Absorbed power 1st speed (W) | 1470 | Weight (Kg) | 218 |
| Frequency (Hz) | 50 | Delivery 1st speed (l/s) | 3056 |
| Insulation Class | I° | Delivery 1st speed (m ³ /h) | 11100 |
| Max ambient temperature for continuous operation (°C) | 90 | Max delivery at max speed (l/s) | 3556 |
| Max. absorbed Current at max. speed (A) | 3,45 | Max delivery at max speed (m ³ /h) | 12800 |
| Max. absorbed Current at min. speed (A) | 2,45 | Pressure - 1st speed (mmH2O) | 42 |
| Max. absorbed power at max speed (W) | 1880 | Pressure - 1st speed (Pa) | 412 |
| Motor IP protection | 55 | Pressure max - max speed (mmH2O) | 59 |
| Nominal Diameter (mm) | 560 | Pressure max - max speed (Pa) | 579 |
| | | RPM max | 920 |

| | | | |
|-----------------------|-----|-------------------------------------|-----|
| Number of Phases (Ph) | 3 | RPM min | 710 |
| Number of Poles | 6 | Sound Pressure level Lp [dB (A)] 3m | 80 |
| Voltage (V) | 400 | | |

Interested?

If you are interested in this product, contact us or locate your nearest Vortice dealer.

[CONTACT US](#)

Documentation


You can see all the documentation relating to this product: price list, information booklet and wiring diagram.

[DOCUMENTATION](#)

d

Accessories


Discover accessories related to the product



TR-G 100/150/180/210 6-8P(GRIGLI APROT.)

- Intake port protection grille for use when the unit is mounted within reach.

[Go to data sheet](#) d



TR-CU 100/150/180/210 6-8P(CONTROT.BASE)

- Installation base counter-frame.

[Go to data sheet](#) d



TR-CVT (COMMUTATORE VELOCITA' TRIF.)

- Single-phase speed controller with 3-position selector (0 - 1 - 2).

[Go to data sheet](#) d



IRET 6

- Three-phase electronic speed controller

[Go to data sheet](#) d

[Find distributor](#)

d

[Register for the Newsletter](#)

d

[Contact us](#)

d

Select country:

International Italy United Kingdom China Latam
