

[←](#) BACK

CODE 15184

# TORRETTA TRT 20 E-V 4P

Centrifugal roof fans with vertical discharge



- [Description](#)
- [Certifications](#)
- [Technical Data Sheet](#)
- [Accessories](#)

DOCUMENTATION

1

[PRODUCTS](#) > [INDUSTRIAL VENTILATION](#) > [ROOF FANS](#) > [ROOF](#)

## Description

- Base manufactured from phosphated pressed steel, epoxy powder coated with hammered effect finish, guaranteeing long-term resistance to atmospheric agents.
- Aerodynamically contoured inlet port for optimum performance, fashioned as a single unit with the base and gauged to optimize air flow.
- Pressed steel motor cover: pickled and phosphated surface, polyester powder coated and oven baked finish, colour grey, with hammered texture.
- Pressed steel side baffles angled to exhaust extracted air upwards: zinc-coated, pickled and phosphated surface, polyester powder coated and oven baked finish, colour grey, with hammered texture.

[Read full description](#)

## Certifications

 CE

 EAC

# Technical Data Sheet

Technical and performance data    Dimensions

---

Absorbed Current max (A)	0,60	Number of Poles	4
Absorbed Power max (W)	300	Voltage (V)	400
Frequency (Hz)	50	Weight (Kg)	43
Insulation Class	I°	Delivery max (l/s)	750
Max ambient temperature for continuous operation (°C)	90	Delivery max (m³/h)	2700
Motor IP protection	55	Pressure max (mmH2O)	35
Nominal Diameter (mm)	250	Pressure max (Pa)	343
Number of Phases (Ph)	3	RPM	1400
		Sound Pressure level Lp [dB (A)] 3m	62

## Interested?

If you are interested in this product, contact us or locate your nearest Vortice dealer.

[CONTACT US](#)

## Documentation

You can see all the documentation relating to this product: price list, information booklet and wiring diagram.

[DOCUMENTATION](#)

»

## Accessories


Discover accessories related to the product



### IRT 15

- Three-phase speed controller


[Go to data sheet](#) **d**



### TR-S 20/30/50 (SERRANDA A GRAVITA')

- Galvanized sheet-metal gravity backdraught shutter.
- With aluminium shutters and return spring, for preventing air backdraughts or penetration of rain when the unit ...

[Go to data sheet](#) **d**



### TR-CU 20/30/50 (CONTROTELAIO DI BASE U)

- Installation base counter-frame.

[Go to data sheet](#) **d**



### TR-B 20/30/50 (BOCCAGLIO ASPIRAZIONE)

- Intake nozzle to fit on intake side for optimizing intake and reducing noise level.

[Go to data sheet](#) **d**

[Find distributor](#) **d**

[Register for the Newsletter](#) **d**

[Contact us](#) **d**

[Work with us](#) [Technical area](#) [Privacy](#) [Sitemap](#)

Select country:

[International](#) [Italy](#) [United Kingdom](#) [China](#) [Latam](#)

© 2019 Vortice - All Rights Reserved - P.iva IT04474410968

Websolute