

Cookies help us to provide our services. By using these services, you accept our use of cookies. [Info](#)

[←](#) BACK

CODE 11321

M 120/5" A

Wall/window axial fans

- [→ Description](#) [→ Certifications](#)
- [→ Technical Data Sheet](#) [→ Accessories](#)

DOCUMENTATION ↓



1 2 3 4

other images 

PRODUCTS > RESIDENTIAL VENTILATION > AXIAL FANS > WALL / WINDOW







Description

- Material: UV resistant plastic (prevents ageing caused by exposure to sunlight).
- Nominal diameter 120 mm.
- Motor protected against thermal overload, with shaft turning in self-lubricating bushings, coupled to screw type thermoplastic impeller with wing profile blades.
- Maximum air flow: 175 m³/h.
- Equipped with system by which the louvres of the grille are opened and closed automatically.

• IMQ SAFETY and IMQ PERFORMANCE certifications.

[Read full description](#)

Certifications

	IMQ	
	CE	↓
	IMQ Performance	
	CCC	
	EAC	
	G-Mark	



Technical Data Sheet

Technical and performance data

Energy data

Dimensions

Curves

Absorbed Current max (A)	0,12	Ø Discharge Hole (mm)	119
Absorbed Power max (W)	20	Voltage (V)	220-240
Frequency (Hz)	50	Weight (Kg)	0,8
Inlet	Automatico	Delivery max (l/s)	48,6
Insulation Class	II°	Delivery max (m ³ /h)	175
IP	X4	Pressure max (mmH2O)	4,5
Max ambient temperature for continuous operation (°C)	50	Pressure max (Pa)	44
Nominal Diameter (mm)	120	RPM	2100
		Sound Pressure level Lp [dB (A)] 3m	39,5

Interested?

If you are interested in this product, contact us or locate your nearest Vortice dealer.

[CONTACT US](#)

Documentation

You can see all the documentation relating to this product: price list, information booklet and wiring diagram.

[DOCUMENTATION](#)



Accessories

Discover accessories related to the product



SCNRB SCAT.COM.NON REV.INCASSO

• Non-reversible electronic speed controller. • Built-in.

[Go to data sheet](#) →



F 120/5"

• Window mounting kit.

[Go to data sheet](#) →



S 120/5

• Ceiling kit made of soft rubber to prevent water infiltration and to maintain IPX4 protection on all surfaces.

[Go to data sheet](#) →



KIT SCB (TRASF.E.C.)

• Built-in controller adaptor.

[Go to data sheet](#) →

[Find distributor](#) →

[Register for the Newsletter](#) →

[Contact us](#) →

[Work with us](#) [Technical area](#) [Privacy](#) [Sitemap](#)

Select country:

[International](#) [Italy](#) [United Kingdom](#) [China](#) [Latam](#)

© 2019 Vortice - All Rights Reserved - P.iva IT04474410968

Websolute