

# Technical Data Sheet


CODE 61756

## NORDIK EVOLUTION R 120/48" NERO

Reversible ceiling fans




### Certifications



### TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50	Delivery max (m <sup>3</sup> /h)	13810
Insulation Class	I°	Delivery max (m <sup>3</sup> /min)	230,17
Voltage (V)	220-240	RPM	198
Airflow speed at max speed (m/s)	2,36	Service value (m <sup>3</sup> /min)/W	3,288
		Sound power level Lw [dB(A)]	49,1

### DIMENSIONS



Etichetta Energetica	NO
Size A (mm)	980
Size B (mm)	298
Size C (mm)	495
Size D (mm)	229
Size E (mm)	724
Size F (mm)	291
Size G (mm)	145
Size H (mm)	640
Size L (mm)	291

#### PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: [prevendita@vortice-italy.com](mailto:prevendita@vortice-italy.com)

# Technical Data Sheet

CODE 61756

## NORDIK EVOLUTION R 120/48" NERO



Reversible ceiling fans

### DESCRIPTION

- Nominal diameter of blades 1200 mm
- Top and bottom motor covers moulded from heat-resistant and UV-resistant thermoplastic resin (ABS), colour black.
- Wiring connections at end of ceiling rod concealed by domes moulded from impact- and UV-resistant thermoplastic resin (PP).
- Single phase start capacitor motor with external rotor, and shaft turning in ball bearings. Direction of rotation reversible.
- Maximum air flow 13810 m<sup>3</sup>/h
- 3 galvanized sheet steel blades powder coated with scratch-resistant polyester, colour black.
- Steel ceiling rod with scratch-resistant polyester powder coated finish, colour black, length 375 mm.
- Bag of accessories containing nuts and bolts required for assembly of blades, ceiling hook and rubber anti-vibration washer.
- Factory-prepared to accept 2 specific optional light kits:
  - with lamp rated 105 W max, E27 screw fitting
  - with 2x15 W max energy saving lamp, E27 screw fitting (mandatory in EU).
- Speed selectable by way of control units or Telenordik 5TR remote control (optional)

### ACCESSORIES



EVOLUTION  
LIGHT KIT  
Code 22413



EVOLUTION  
LIGHT KIT ES  
Code 22414



SCRR5  
Code 12963



SCRR5L  
Code 12964

#### PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)  
Pre & Post Vendita: fax +39 02 90699302  
Email prevendita: [prevendita@vortice-italy.com](mailto:prevendita@vortice-italy.com)