


Technical Data Sheet

CODE 40456

E 302 T

Low-pressure plate axial fans




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed Current at 220 V (A)	0,78	Max Temperature of Exhaust Air (Continuous Operation)	70
Absorbed Current at 240 V (A)	0,95	Motor IP protection	44
Absorbed Current at 380 V (A)	0,44	Nominal Diameter (mm)	315
Absorbed Current at 415 V (A)	0,55	Number of Poles	2
Absorbed Current max (A)	0,95	Voltage (V)	220/380 240/415
Absorbed power at 220-380 V (W)	180	Weight (Kg)	3,5
Absorbed power at 240-415 V (W)	200	Delivery max (l/s)	667
Absorbed Power max (W)	200	Delivery max (m ³ /h)	2400
Frequency (Hz)	50	Pressure max (mmH ₂ O)	32,5
Insulation Class	I°	Pressure max (Pa)	319
Max ambient temperature for continuous operation (°C)	70	RPM	2800
		Sound Pressure level Lp [dB (A)] 3m	65

DIMENSIONS



Diametro \emptyset (mm)	315
Size A (mm)	380
Size B (mm)	330
Size C (mm)	254
Size D (mm)	\emptyset
	308
Size D3 (mm)	\emptyset
	300
Size E (mm)	70
Size F (mm)	8
Size G (mm)	10

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 40456

E 302 T

Low-pressure plate axial fans



DESCRIPTION

- Nominal diameter 300 mm
- Wall-mounting panel manufactured from phosphated pressed steel, polyester powder coated with hammered effect finish, guaranteeing long-term resistance to atmospheric agents.
- Ventilation port fashioned in one piece with the panel and gauged to optimize air flow.
- Protective grille (in accordance with UNI ISO 13857 standard) combining the function of motor bracket, made of electrically welded steel with epoxy paint finish, colour black. Easy removal simplifies maintenance and cleaning of the fan.
- 1 speed asynchronous three-phase AC motor with shaft turning in double shielded ball bearings, insulation class F.
- Maximum air flow: 2,400 m³/h.
- Impeller with 6 wing profile blades keyed to a diecast aluminium hub and dynamically balanced (UNI ISO 1940 – Balancing class 6.3), optimized to deliver maximum performance and low noise levels, moulded from filled polypropylene for superior dimensional stability and resistance to atmospheric agents.
- Vortice speed controller.

ACCESSORIES




IRT 15

Code 12923



**PGR 300
(PERSIANA
GRAVITA')**

Code 50250



**TRA 300
(TELAIO CON
RETE ANTINF.)**

Code 51250



**DPU 300
(DISTANZIATORE)**

Code 52251



**IRET INVERTER
2,5 M**

Code 12816

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com