

Technical Data Sheet

CODE 61742

NORDIK INTERNATIONAL PLUS-R 140/56"IPX5



Ceiling fans



Certifications



IMQ



CE




EAC

TECHNICAL AND PERFORMANCE DATA

| | | | |
|--------------------------|------|---------------------------------------|---------|
| Absorbed Current max (A) | 0,33 | Voltage (V) | 220-240 |
| Absorbed Power max (W) | 70 | Weight (Kg) | 6,70 |
| Blades diameter | 1422 | Airflow speed at max speed (m/s) | 1,69 |
| Frequency (Hz) | 50 | Delivery max (m ³ /h) | 13500 |
| Insulation Class | I° | Delivery max (m ³ /min) | 225,00 |
| IP | X5 | RPM | 231 |
| Motor Power (W) | 70 | Service value (m ³ /min)/W | 3,214 |
| | | Sound power level Lw [dB(A)] | 52,1 |

DIMENSIONS



| | |
|-------------|-------|
| Size A (mm) | ∅ |
| | 1422 |
| Size B (mm) | ∅ 230 |
| Size C (mm) | 495 |

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 61742

NORDIK INTERNATIONAL PLUS-R 140/56"IPX5



Ceiling fans

DESCRIPTION

- Nominal diameter of blades 1400 mm
- Top and bottom motor covers moulded from heat-resistant and UV-resistant thermoplastic resin (ABS), colour white
- Wiring connections at end of ceiling rod concealed by domes moulded from impact- and UV-resistant PP, colour white.
- Single phase start capacitor motor with external rotor, and shaft turning in ball bearings. Direction of rotation reversible.
- Maximum air flow: 13,500 m³/h.
- 3 galvanized sheet steel blades powder coated with scratch-resistant polyester, colour white.
- Steel ceiling rod with polyester powder coated finish, colour white, length 375 mm.
- Bag of accessories containing nuts and bolts required for assembly of blades, ceiling hook and rubber anti-vibration washer.
- Speed selectable by way of control units (optional)
- Enclosure rating IPX5 ensuring complete protection from water spray.

ACCESSORIES



SCRR5

Code 12963



SCRR/M

Code 12965



KIT

SCBRR5/5L/M

Code 22489



SC 503 B

Code 12801



SC 503 N

Code 12802



SC EXT B

Code 12803



PSC-B

Code 22463



PSC-W

Code 22462



ASTA NK I 200

BIANCA

Code 22032



ASTA NK I 250

BIANCA

Code 22033



ASTA NK I 350

BIANCA

Code 22042

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com



ASTA NK I 500

BIANCA

Code 22051

ASTA NK I 750

BIANCA

Code 22074

ASTA NK I 1000

BIANCA

Code 22077

VORT DELTA T

Code 13039