

Technical Data Sheet

CODE 61750

NORDIK EVOLUTION R 90/36" BIANCO

Reversible ceiling fans



Certifications



TECHNICAL AND PERFORMANCE DATA

| | | | |
|--------------------------|---------|---------------------------------------|--------|
| Absorbed Current max (A) | 0,34 | Weight (Kg) | 6,4 |
| Absorbed Power max (W) | 70 | Airflow speed at max speed (m/s) | 3,52 |
| Blades diameter | 980 | Delivery max (m ³ /h) | 11592 |
| Frequency (Hz) | 50 | Delivery max (m ³ /min) | 193,20 |
| Insulation Class | I° | RPM | 200 |
| Voltage (V) | 220-240 | Service value (m ³ /min)/W | 2,760 |
| | | Sound power level Lw [dB(A)] | 46,1 |

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 61750

NORDIK EVOLUTION R 90/36" BIANCO



Reversible ceiling fans

DESCRIPTION

- Nominal diameter of blades 900 mm
- Top and bottom motor covers moulded from heat-resistant and UV-resistant thermoplastic resin (ABS), colour white.
- Wiring connections at end of ceiling rod concealed by domes moulded from impact- and UV-resistant thermoplastic resin (PP).
- Single phase start capacitor motor with external rotor, and shaft turning in ball bearings. Direction of rotation reversible.
- Maximum air flow 11592 m³/h
- 3 galvanized sheet steel blades powder coated with scratch-resistant polyester, colour white.
- Steel ceiling rod with scratch-resistant polyester powder coated finish, colour white, length 375 mm.
- Bag of accessories containing nuts and bolts required for assembly of blades, ceiling hook and rubber anti-vibration washer.
- Factory-prepared to accept 2 specific optional light kits:
 - ? with lamp rated 105 W max, E27 screw fitting
 - ? with 2x15 W max energy saving lamp, E27 screw fitting (mandatory in EU).
- Speed selectable by way of control units or Telenordik 5TR remote control (optional)

ACCESSORIES



ASTA NK I 200 BIANCA

Code 22032



ASTA NK I 250 BIANCA

Code 22033



ASTA NK I 350 BIANCA

Code 22042



ASTA NK I 500 BIANCA

Code 22051



ASTA NK I 750 BIANCA

Code 22074



ASTA NK I 1000 BIANCA

Code 22077



EVOLUTION LIGHT KIT

Code 22413



EVOLUTION LIGHT KIT ES

Code 22414



SCRR5

Code 12963



SCRR5L

Code 12964



SCRR/M

Code 12965

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com





**TELENORDIK
5TR**

Code 22386



**KIT
SCBRR5/5L/M**

Code 22489



**SET PALE NK I
PLUS 90/36
BIANCO INT.**

Code 22631



SC 503 B
Code 12801



SC 503 N
Code 12802



SC EXT B
Code 12803



PSC-W
Code 22462



PSC-B
Code 22463



SCI503
Code 22461