

[← BACK](#)

CODE 60621

# GORDON C40/16" N

Oscillating table, wall-mounting and pedestal fans

[→ Description](#)[→ Certifications](#)[→ Technical Data Sheet](#)[DOCUMENTATION](#)

[PRODUCTS](#) > [SUMMER VENTILATION](#) > [OSCILLATING FANS](#) > [FLOOR](#)

## Description

- Material: plastic resin able to withstand aging induced by exposure to sunlight (UV-resistant), and formulated with an antistatic compound to prevent accumulation of dust, colour black.
- Nominal diameter 400 mm
- 3 speed asynchronous motor with thermal overload protection and shaft turning in self-aligning and self-lubricating bushings, coupled to oscillating mechanism generating movement through an angle of approx 90° maximum
- Motor housing equipped with hinge and clamp knob for adjustment of tilt angle.
- On/off switch and speed selector (rotary control incorporated into rear

[Read full description](#)

## Certifications



IMQ



CE



EAC



## Technical Data Sheet

### Technical and performance data    Dimensions

Absorbed Current max (A)	0,19	Airflow speed at max speed (m/s)	1,61
Absorbed Power max (W)	40	Delivery max (m <sup>3</sup> /h)	4000
Frequency (Hz)	50-60	Delivery max (m <sup>3</sup> /min)	66,67
Insulation Class	II°	giri_minuto	1145
Max. absorbed power at max speed (W)	40	RPM	1145
Voltage (V)	220-240	Service value (m <sup>3</sup> /min)/W	1,667
Weight (Kg)	5,4	Sound power level Lw [dB(A)]	57,2

## Interested?

If you are interested in this product, contact us or locate your nearest Vortice dealer.

## Documentation

You can see all the documentation relating to this product: price list, information booklet and wiring

[CONTACT US](#)

[DOCUMENTATION](#)



[Find distributor](#) →

[Register for the Newsletter](#) →

[Contact us](#) →

[Work with us](#) [Technical area](#) [Privacy](#) [Sitemap](#)

**Select country:**

[International](#) [Italy](#) [United Kingdom](#) [China](#) [Latam](#)