

Cookies help us to provide our services. By using these services, you accept our use of cookies. [Info](#)

[←](#) BACK

CODE 60615

GORDON 40/16"

Oscillating table, wall-mounting and pedestal fans

- Description
- Certifications
- Technical Data Sheet



DOCUMENTATION



[PRODUCTS](#) > [SUMMER VENTILATION](#) > [OSCILLATING FANS](#) > [TABLE](#)

Description

- Material: plastic resin able to withstand aging induced by exposure to sunlight (UV-resistant), and formulated with an antistatic compound to prevent accumulation of dust.
- Nominal diameter 400 mm
- 3 speed asynchronous motor with thermal overload protection and shaft turning in self-aligning and self-lubricating bushings, coupled to oscillating mechanism generating movement through an angle of approx 90° maximum.
- Motor housing equipped with hinge and clamp knob for adjustment of tilt angle.
- Rotary on/off switch and fan speed selector

[Read full description](#)

Certifications



IMQ



CE



EAC



Technical Data Sheet

Technical and performance data Dimensions

Absorbed Current max (A)	0,19	Delivery 3rd speed (m ³ /h)	4000
Absorbed Power max (W)	40	Delivery max (m ³ /h)	4000
Frequency (Hz)	50-60	Delivery max (m ³ /min)	66,67
Insulation Class	II°	Max delivery at max speed (m ³ /h)	4000
Voltage (V)	220-240	RPM	1145
Weight (Kg)	2,7	Service value (m ³ /min)/W	1,667
Airflow speed at max speed (m/s)	1,61	Sound power level Lw [dB(A)]	57,2

Interested?

If you are interested in this product, contact us or locate your nearest Vortice dealer.

Documentation

You can see all the documentation relating to this product: price list, information booklet and wiring

[CONTACT US](#)

[DOCUMENTATION](#)



[Find distributor](#) →

[Register for the Newsletter](#) →

[Contact us](#) →

[Work with us](#) [Technical area](#) [Privacy](#) [Sitemap](#)

Select country:

[International](#) [Italy](#) [United Kingdom](#) [China](#) [Latam](#)