



VORTICEL A-E ES RANGE

INDUSTRIAL WALL-MOUNTED AXIAL FANS





VORTICE S.p.A. is part of a multinational group,^[1] **VORTICE GROUP**, which operates through its own companies or local distributors in over 90 countries worldwide and has a rich product portfolio that guarantees air quality and climate comfort. The headquarters of VORTICE S.p.A are in Tribiano (Milan).



VORTICE GROUP also includes:

[1/2]

BUSINESS UNIT INDUSTRIAL, born from the acquisition in 2010 of Loran srl, based in Isola della Scala (VR). 2024 become Vortice's BUSINESS UNIT INDUSTRIAL.

[3]

VORTICE LIMITED, the UK subsidiary of VORTICE S.p.A., established in 1977 and based in Burton on Trent.

[4]

VORTICE VENTILATION SYSTEM, a company inaugurated in 2013 with headquarters in Changzhou, China.

[5]

CASALS VENTILACIÓN AIR INDUSTRIAL S.L., historic Spanish brand, based in Sant Joan de les Abadesses, Girona, acquired in 2019.

[6]

VORTICE LATAM S.A., based in Alajuela in Costa Rica, established in 2012.

[7]

VORTICE POLSKA new representative office in Warsaw, Poland, established in 2026.



VORTICEL A-E ES RANGE

Industrial wall-mounted axial fans

Versatile and suitable for a wide range of industrial and commercial applications, their compact dimensions allow them to be easily integrated into various fields of application, from refrigeration to air conditioning, from ventilation to renewable energy generation systems, where high air flow rates are required alongside relatively low pressure drops. Their precisely calibrated drives and advanced control technology ensure efficient operation.



Regulatory Standards

Products of the VORTICEL A-E ES Range series comply with the following European Standards, Directives and Regulations:

- **Machine Safety Standards:**

- UNI EN ISO 12100:2010
- CEI EN 60204-1:2018
- UNI EN ISO 13857:2020
- UNI EN ISO EN 12499:2019
- CEI EN 60529:1997

- **Electromagnetic Compatibility Standards:**

- EN IEC 61000-6-4:2019
- EN IEC 61000-6-2:2019
- EN IEC 61000-3-2:2019

- **European Directives and Regulations for CE Marketing:**

- EMC Directive 2014/30/UE
- RED Directive (2014/53/UE)
- Ecodesign Directive (2009/125/CE)
- RoHS Directive 2011/65/EU + RoHS 3 Amendment 2015/863
- Machinery Regulation (UE) 2023/1230
- Electric Motors Regulation (EU) 2019/1781
- Fans Regulation (UE) 2024/1834
- REACH Regulation (EC) 1907/2006

TECHNICAL FEATURES


High efficiency industrial wall mounted axial fans with reduced axial depth, available in diameters from 250 to 630 mm and airflow rates up to 14.500 m³/h.

- **Range Composition:**
12 models: 9 single phase and 3 three phase.
- **Construction:**
Panels made of powder coated black painted steel.
- **Inlet nozzles:**
Integrated with the panels, calibrated to optimize airflow; elongated profile to improve performance and allow easy connection to ducting.
- **Protection grilles:**
Compliant with UNI ISO 13857, made of welded steel rings, powder coated black.
- **Motors:**
EC motors integrated with driver, external rotor type to minimize axial length, shafts mounted on ball bearings, thermally protected and speed controllable via 0–10 V signal.
- **Impellers:**
Dynamically balanced impellers (UNI ISO 1940, grade 6.3); plastic blades, optimised in shape to ensure high performance, high efficiency and low noise levels.

KEY FEATURES

- **High efficiency and performance:**
Electronic (EC) motors are reliable and quiet, making VORTICEL A E ES fans ideal for applications requiring high airflow at low static pressure. Perfectly aligned with modern environmental standards, they combine low power consumption with easy speed control, allowing airflow adjustment to actual needs without costly additional devices, ensuring long term efficiency and cost effectiveness.
- **High reliability:**
Optimized construction for continuous operation in industrial environments, even at high ambient temperatures.
- **Full compliance with the latest European regulations**, including Regulation (EU) 2024/1834, effective from 24 July 2026, which introduces stricter minimum efficiency requirements for fans sold in EU countries (with limited exceptions).
- **Installation flexibility:** Suitable for installation in any orientation.
- **Reduced axial depth.**

Dimensions



	MODELS	COD.	Ø	A	B	C	D	ØE
TYPE A	SINGLE-PHASE							
	A-E 250 M ES	41220	250	370	370	102.6	320	7
	A-E 300 M ES	41221	300	430	430	86.8	380	10
	A-E 350 M ES	41222	350	485	485	125	435	10
	A-E 400 M ES	41223	400	540	540	148.7	490	10
	A-E 450 M ES	41224	450	575	575	153	520	10
	A-E 500 M ES-A	41225	500	665	665	184.2	610	12
	A-E 500 M ES-B	41226	500	665	665	190.5	610	12
	A-E 550 M ES	41228	550	725	725	193	670	12
	A-E 630 M ES	41230	630	805	805	208.5	750	10
TYPE B	THREE-PHASE							
	A-E 500 T ES	41227	500	725	725	183	670	12
	A-E 550 T ES	41229	550	725	725	183	670	12
	A-E 630 T ES	41231	630	805	805	216	750	10

Dimensions in mm

VORTICEL A-E ES RANGE
Industrial wall-mounted axial fans

TECHNICAL DATA

MODELS	Code	Motor Class	V~50/60 Hz	(W)	(A) Max	RPM	Max Airflow m³/h	Pa	Sound Pressure Lp dB(A) 1m	kg	IP	Outside temperature Max °C	Outside temperature Min °C
SINGLE-PHASE													
A-E 250 M ES	41220	B	220-240	200	1,4	3150	1500	208	69	4,5	44	+60	-20
A-E 300 M ES	41221	B	220-240	165	1,2	2100	1980	147	65	3	44	+60	-20
A-E 350 M ES	41222	B	220-240	165	1,1	1550	2825	143	67	6,5	44	+60	-20
A-E 400 M ES	41223	B	220-240	330	1,5	1650	4830	183	69	6	54	+60	-20
A-E 450 M ES	41224	B	220-240	340	1,57	1700	5540	165	70	6,5	44	+60	-20
A-E 500 M ES-A	41225	B	220-240	200	1,4	900	4850	98	56	10	54	+60	-20
A-E 500 M ES-B	41226	F	220-240	500	2,45	1450	7450	195	71	18	55	+60	-20
A-E 550 M ES	41228	F	220-240	550	2,6	1250	7350	210	71	6,5	44	+60	-20
A-E 630 M ES	41230	F	220-240	600	2,75	960	10.300	185	65	18	55	+60	-20
THREE-PHASE													
A-E 500 T ES	41227	F	380-415	850	1,5	1690	8700	270	78	18	44	+60	-20
A-E 550 T ES	41229	F	380-415	950	1,65	1690	9200	243	78	14	54	+60	-20
A-E 630 T ES	41231	F	380-415	780	1,3	1250	11.000	195	69	14	44	+60	-20

6

ENERGY EFFICIENCY DATA ACCORDING TO REG. (EU) 2024/1834

PRODUCT NAME AND CODE	A-E 250 M ES 41220	A-E 300 M ES 41221	A-E 350 M ES 41222	A-E 400 M ES 41223	A-E 450 M ES 41224	A-E 500 M ES-A 41225
Address at which the manufacturer can be contacted:	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy
Applicable pressure difference [Pa]:	183	98	72	147	130	62
DC voltage lower than 100V:	False	False	False	False	False	False
Efficiency category:	Static	Static	Static	Static	Static	Static
Efficiency grade N at BEP:	63	51	50	51	54	59
Fan efficiency [%]:	43,9	32,1	31,8	36,8	39,8	40,3
Fan speed in revolutions per minute [RPM]:	2945	1934	1530	1720	1638	840
Fan type:	axial fan	axial fan	axial fan	axial fan	axial fan	axial fan
List of all significant elements:	see the instruction booklet	see the instruction booklet	see the instruction booklet	see the instruction booklet	see the instruction booklet	see the instruction booklet
Manufacturer's name:	Vortice SpA	Vortice SpA	Vortice SpA	Vortice SpA	Vortice SpA	Vortice SpA
Measurement category:	A	A	A	A	A	A
Special characteristics:	no	no	no	no	no	no
Special speed:	no	no	no	no	no	no
The electric input power Pe [kW]:	0,142	0,170	0,177	0,411	0,426	0,184
The specific ratio:	1	1	1	1	1	1
Use of a VSD:	integrated	integrated	integrated	integrated	integrated	integrated
Volume flow rate qv [m³/h]:	879	1446	2055	2854	3620	3128






ENERGY EFFICIENCY DATA ACCORDING TO REG. (EU) 2024/1834

PRODUCT NAME AND CODE	A-E 500 M ES-B 41226	A-E 500 T ES 41227	A-E 550 M ES 41228	A-E 550 T ES 41229	A-E 630 M ES 41230	A-E 630 T ES 41231
Address at which the manufacturer can be contacted:	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy	Vortice SpA Starda Cerca 2 20067 Tribiano (MI) Italy
Applicable pressure difference [Pa]:	140	187	106	172	74	102
DC voltage lower than 100V:	False	False	False	False	False	False
Efficiency category:	Static	Static	Static	Static	Static	Static
Efficiency grade N at BEP:	54	52	51	51	52	53
Fan efficiency [%]:	41,1	40,9	37,0	39,7	38,1	40,6
Fan speed in revolutions per minute [RPM]:	1424	1720	1231	1450	941	1095
Fan type:	axial fan	axial fan	axial fan	axial fan	axial fan	axial fan
List of all significant elements:	see the instruc- tion booklet	see the instruc- tion booklet	see the instruc- tion booklet	see the instruc- tion booklet	see the instruc- tion booklet	see the instruc- tion booklet
Manufacturer's name:	Vortice SpA	Vortice SpA	Vortice SpA	Vortice SpA	Vortice SpA	Vortice SpA
Measurement category:	A	A	A	A	A	A
Special characteristics:	no	no	no	no	no	no
Special speed:	no	no	no	no	no	no
The electric input power Pe [kW]:	0,585	0,892	460	855	460	704
The specific ratio:	1	1	1	1	1	1
Use of a VSD:	integrated	integrated	integrated	integrated	integrated	integrated
Volume flow rate qv [m³/h]:	4854	5612	4589	5771	6708	8448


VORTICEL A-E ES RANGE
Industrial wall-mounted axial fans

PERFORMANCE AND CONSUMPTION CURVES


A-E 250 M ES
Cod.41220




A-E 300 M ES
Cod.41221



A-E 350 M ES
Cod.41222




A-E 400 M ES
Cod.41223




Flow rate/Power	Flow rate / Pressure
— 10V	— 10V
— 6V	— 6V
— 4V	— 4V

A-E 450 M ES
Cod.41224



A-E 500 M ES-A
Cod.41225



Flow rate/Power	Flow rate / Pressure
— 10V	— 10V
— 6V	— 6V
— 4V	— 4V


Flow rate/Power	Flow rate / Pressure
— 10V	— 10V
— 7V	— 7V
— 5V	— 5V






PERFORMANCE AND CONSUMPTION CURVES


A-E 500 M ES-B
Cod.41226




A-E 550 M ES
Cod.41228



A-E 630 M ES
Cod.41230




A-E 500 T ES
Cod.41227




Flow rate/Power	Flow rate / Pressure
10V	10V
6V	6V
4V	4V

A-E 550 T ES
Cod.41229



A-E 630 T ES
Cod.41231



Flow rate/Power	Flow rate / Pressure
10V	10V
7V	7V
5V	5V


VORTICEL A-E ES RANGE
Industrial wall-mounted axial fans

ACCESSORIES

MODELS	CODE	DPU SPACER	POT - POTENTIOMETER	TRA - SAFETY GRILLE	PGR/PGR-P GRAVITY SHUTTER
SINGLE-PHASE					
A-E 250 M ES	41220	•	•	•	•
A-E 300 M ES	41221	•	•	•	•
A-E 350 M ES	41222	•	•	•	•
A-E 400 M ES	41223	•	•	•	•
A-E 450 M ES	41224	•	•	•	•
A-E 500 M ES-A	41225		•	•	•
A-E 500 M ES-B	41226		•	•	•
A-E 550 M ES	41228		•	•	•
A-E 630 M ES	41230		•	•	•
THREE-PHASE					
A-E 500 T ES	41227		•	•	•
A-E 550 T ES	41229		•	•	•
A-E 630 T ES	41231		•	•	•

10

DPU - SPACER



Model	Code	DPU - SPACER	Code
A-E 250 M ES	41220	DPU 250	52152
A-E 300 M ES	41221	DPU 300	52252
A-E 350 M ES	41222	DPU 350	52352
A-E 400 M ES	41223	DPU 400	52452
A-E 450 M ES	41224	DPU 450	52551

POT - POTENTIOMETER


Cod.12828

Wall-mounted and flush-mounted (in a standard DIN box) 0–10 V potentiometer.







TRA - FRAME WITH PROTECTIVE SAFETY NET



Model	Code	TRA - Frame with safety net	Code
A-E 250 M ES	41220	TRA 250	51150
A-E 300 M ES	41221	TRA 300	51250
A-E 350 M ES	41222	TRA 350	51350
A-E 400 M ES	41223	TRA 400	51450
A-E 450 M ES	41224	TRA 450/500	51550
A-E 500 M ES- A	41225		
A-E 500 M ES-B	41226		
A-E 500 T ES	41227		
A-E 550 M ES	41228	TRA 500	51600
A-E 550 T ES	41229		
A-E 630 M ES	41230	TRA 630	51680
A-E 630 T ES	41231		

PGR/PGR-P - GRAVITY SHUTTER

11



Model	Code	PGR - Gravity shutter	Code
A-E 250 M ES	41220	PGR 250	50150
A-E 300 M ES	41221	PGR 300	50250
A-E 350 M ES	41222	PGR 350	50350
A-E 400 M ES	41223	PGR 400	50400
A-E 450 M ES	41224	PGR 450/500	50550
A-E 500 M ES- A	41225		
A-E 500 M ES-B	41226		
A-E 500 T ES	41227		
A-E 550 M ES	41228	PGR-P 560	50465
A-E 550 T ES	41229		
A-E 630 M ES	41230	PGR-P 630	50466
A-E 630 T ES	41231		

VORTICE GROUP COMPANIES

VORTICE S.P.A

Strada Cerca, 2
District of Zoate
20067 Tribiano
(Milan) Italy
Tel. (+39) 02 906991
vortice.com
V.A.T. IT 04474410968

BUSINESS UNIT INDUSTRIAL

Via B. Brugnoli 3,
37063 Isola della Scala
(Verona) Italy
Tel. (+39) 045 6631042
vorticeindustrial.com
V.A.T. IT 04474410968

VORTICE LIMITED

Beeches House
Eastern Avenue
Burton on Trent
DE13 0BB United Kingdom
Tel. (+44) (0) 1283-49.29.49
vortice.ltd.uk

CASALS VENTILACIÓN AIR INDUSTRIAL S.L.

Ctra. Camprodon, s/n 17860
Sant Joan de les Abadesses
(Girona) Spain
Tel. (+34) 972720150
casals.com

VORTICE LATAM S.A.

Bodega #6
Zona Franca Bes Alajuela,
Alajuela 20101
Costa Rica
Tel. (+506) 2201.6934
vortice-latam.com

VORTICE VENTILATION SYSTEM

(Changzhou) Co.LTD
No. 388 West Huanghe Road
Building 19, Changzhou
Post Code: 213000 China
Tel. (+86) 0519 88990150
vortice-china.com

VORTICE POLSKA

ul. Cybernetyki 19A,
02-677 Warszawa
Poland
biuropolska@vortice.com
vorticepolska.pl

The descriptions and illustrations in this catalogue are intended to be indicative and not binding. Without prejudice to the essential characteristics of the products described and illustrated here, VORTICE reserves the right to make, at any time and without notice, any changes to parts, aesthetic details or supply of accessories to its products that are deemed to be appropriate for improvement or for any construction or commercial requirement. This printout completely cancels and replaces all previous ones.

